USB 3.0 HUB avec 4 ports, version DIN RAIL, boîtier métallique, EX-1186HMVS-2

Numéro d'article EX-1186HMVS-2

Description du produit

USB 3.0 HUB concentrateur avec 4 ports, version DIN RAIL, 1x B femelle (entrée) + 4x A femelle (sorties), boîtier métallique, avec protection de surintensité, sans alimentation électrique, couleur: noir, EXSYS EX-1186HMVS-2

Product information

The rugged, industry standard EX-1186HMVS-2 USB hub with four USB 3.2 Gen 1 (previously called USB 3.0) outputs screwable and 15KV ESD overvoltage protection can be installed on the wall or on a 19-inch rack. The EX-1186HMVS-2 simultaneously supports 1.5A power for each port to charge iPhone, iPad, smartphone and tablets. It connects to a computer or server using the supplied USB 3.2 Gen 1 cable. It supports the Hi-Speed USB 3.0 data transfer rate of up to 5Gbps and is backward compatible to USB 1.1. It can be powered with USB bus power or via a two-wire terminal block connector (+7V to +24V).

- USB 3.2 Gen 1 Metal HUB with four Downstream ports
- 15KV ESD Surge Protection for all ports
- Power +7V up to +24V DC over the Terminal Block or DC Jack
- Power supply optionally also from the USB-BUS +5V (Bus-Power)
- Easy installation with the included DIN-Rail Kit
- Compact industrial design
- Automatic recognition the data transfer rate for the attached external devices
- 1.5A current on all 4 ports
- Support USB Battery Charging: CDP and DCP for charge simultaneously iPhone, iPad version 4 or higher, Smartphone and Tablet's
- Automatic detection of input polarity on the current terminal block
- Rugged metal case
- 1 x LED Power Display
- Chipset: Genesys GL3523

Packaging Contents

EX-1186HMVS-2, USB 3.2 Gen 1 Cable, Din-Rail Kit, Manual

- Category: USB HUB
- Interface: USB 3.2 Gen 1
- Connections: A socket
- Number of ports: 4
- Power connection: DC Jack + TB 7V-24V
- Design: Din-Rail
- Surge protection: 15KV ESD
- Housing: Metal
- Colour: black
- Cable: Screwable
- Cable length meter: 1,5
- Application: Industrial
- Charging power total: 30 W

Plus d'images

PWR
V+ V-
7~24V DC
4
3
2
1
USB3.2 Gen 1