Touret de câble USB 3.0, 100m, Qualité Premium, UL, Copartner, noir

Numéro d'article CU-ROL-U3-2
Longueur 100000mm

Description du produit

Rouleau de câble USB 3.0, 100m, Qualité Premium, Copartner AWG 28/28/24, double blindage, UL, couleur: noir

---

.

Plus d'images

COPARTNER

SPECIFICATION: | (1P*28# +D+AL+ Mylar)*2C+1P*28#+2C*24# +AL+B /UL20276

ITEM		SPECIFICATION		
CONDUCTOR	AWG	28AWG	28AWG	24AWG
	MATERIAL	TINNED COPPER	TINNED COPPER	TINNED COPPER
	COND.SIZE	7/0.127±0.008 mm	7/0.127±0.008 mm	7/0.20±0.008 mm
INSULATION	MIN.AVG.THICK	0.23 mm	0.12 mm	0.23 mm
	MATERIAL	FM-PE+SKIN	HD-PE	SR-PVC
	O . D	0.88± 0.05 mm	0.70 ± 0.05 mm	1.10 ± 0.05 mm
	N O.	1P*2	1P	2C
DRAIN	AWG	30AWG	/	/
	MATERIAL	TINNED COPPER	/	/
	SIZE	7/0.10±0.008 mm×1PCS	/	/
Face Inside AL.Mylar	COVERAGE	100%	/	/
	OVERLAP	25% MIN	/	/
MYLAR	COVERAGE	100%	/	/
	OVERLAP	25%MIN	/	/
Face Outside AL.Mylar	COVERAGE	100%		
	OVERLAP	25%MIN		
BRAID	MATERIAL	TINNED COPPER		
	SIZE	16*7/0.10±0.008 mm		
JACKET	MIN.AVG.THICK	0.51 mm		
	MATERIAL	MATT PVC		
	COLOUR	UL813 BLACK		
	O . D	6.00±0.15 mm		

COPARTNER

ELECTRICAL CHARACTERISTICS

USB2.0 UTP

1.Rating Temperature: 80°C Voltage: 30V
2.Conductor Resistance: at 20°Cmax 28AWG: 237.25Ω/km;
24AWG: 93.25Ω/km
3.Insulation resistance: DC-500V 10MΩ -KM MIN at 20°C
4.Propagation Delay Skew:100ps (Full-/High-speed only)
5.Time Delay: 5.2 ns/m (max.)
6.Impedance: 90±15%Ω
7.Attenuation(Full/High-speed only):

F(MHz)	Attenuation(dB)	F(MHz)	Attenuation(dB)	F(MHz)	Attenuation(dB)	F(MHz)	Attenuation(dB)
0.064	0.08	1	0.20	24	0.95	400	5.80
0.256	0.11	4	0.39	48	1.35		
0.512	0.13	8	0.57	96	1.90		
0.772	0.15	12	0.76	200	3.20		

USB3.0 STP*2P

1. Differential Impedance: 90±7Ω
2. Inira-Pair Skew : 15ps / m
3. Attenuation/Insertion Loss:
   1.5dB/2M@0.1GHz
   5.0dB/2M@1.25GHz
   7.5dB/2M@2.5GHz
   25dB/2M@7.5GHz
4. Differential to common mode:
   20dB/cable @ 0.1-7.5GHz
5. NEXT:
   32dB@0.1GHz
   32dB@2.5GHz
   23dB@3.0GHz
   23dB@7.5GHz

COPARTNER



PHYSICAL PROPERTIES OF JACKET

1.Tensile Strength: Unaged: 1500PSI min Aged: 70% min
2. Elongation: Unaged: 100% min Aged: 65%
3. Heat shock test: NO CRACKING
4. Cold bend test: NO CRACKING
5. Deformation test: MAX 50%
6. Flame test: PASS VW-1

USB 3.0 Cable E119932 AWM 20276 80°C 30V
VW-1 COPARTNER

CN-5303
HT